

	PS6000	PQ6000
<b>DISPLAY</b>		
SIZE	50	50 / 42
RESOLUTION	1920 X 1080	1365 X 768 / 1024 X 768
BRIGHTNESS (CD/M2)	1500	1500
DYNAMIC CONTRAST RATIO	2,000,000:1	2,000,000:1
COLOURS REPRODUCTION (R,G,B)	16 BITS	16 BITS
100HZ EQUIVALENT DRIVING	•	•
CORRESPONDING 150HZ EFFECT	•	•
600HZ SUB-FIELD DRIVING	•	•
FILTER TYPE (X-BLACK / GLASS)	GLASS	GLASS
ISM (IMAGE STICKING MINIMIZATION)	• (WHITE WASH/ORBITER/COLOUR WASH)	• (WHITE WASH/ORBITER/COLOUR WASH)
LIFE SPAN (HR)	100,000 (STANDARD MODE/BRIGHTNESS 50% LEVEL/PANEL ONLY)	100,000 (STANDARD MODE/BRIGHTNESS 50% LEVEL/PANEL ONLY)
ANALOG	(PALI/I', PAL/SECAM BG/DK, SECAM L/L', NTSC M(AV ONLY)	(PALI/I', PAL/SECAM BG/DK, SECAM L/L', NTSC M (AV ONLY)
DVB-T	•(CI TYPE)	• (CI TYPE)
DVB-S	-	-
DUAL XD ENGINE	•	•
ASPECT RATIO CORRECTION	8 MODES (16:9/JUST SCAN/ORIGINAL/FULL WIDE/4:3/14:9/ZOOM/CINEMA ZOOM1)	8 MODES (16:9/JUST SCAN/ORIGINAL/FULL WIDE/4:3/14:9/ZOOM/CINEMA ZOOM1)
JUST SCAN (0% OVERSCAN) - WHEN "JUST SCAN MODE" SELECTED	COMPONENT/HDMI 720P/1080i,1080P MPEG4 HD	COMPONENT/HDMI 720P/1080i,1080P MPEG4 HD
ENHANCED LINE DOUBLER	•	•
ENHANCED NOISE REDUCTION	3D NOISE REDUCTION (HIGH/MID/LOW/OFF)	3D NOISE REDUCTION (HIGH/MID/LOW/OFF)
DIGITAL COMB FILTER	3D COMB FILTER	3D COMB FILTER
DLTI (DIGITAL LUMINANCE TRANSIENT IMPROVER)	•	•
DCTI (DIGITAL COLOUR TRANSIENT IMPROVER)	•	•
COLOUR TEMPERATURE CONTROL	• (COOL, MEDIUM, WARM)	• (COOL, MEDIUM, WARM)
BLACK STRETCHER	•	•
REAL CINEMA 24P (3:3 PULL DOWN)	• (HDMI 1080 24P)	• (HDMI 1080 24P)
CINEMA 3:2 / 2:2 PULL DOWN MODE	•	•
ZOOM +/-, SCREEN POSITION	•	•
PICTURE RESET	•	•
PICTURE MODE	7 MODE (VIVID/STANDARD/CINEMA/SPORTS/GAME/ ISF EXPERT/ISF EXPERT2)	7 MODE (VIVID/STANDARD/CINEMA/SPORTS/GAME/ ISF EXPERT/ISF EXPERT2)
PICTURE WIZARD	-	-
XD COLOUR (ACTIVE COLOUR MANAGEMENT)	•	•
<b>AUDIO</b>		
MONO/STEREO/DUAL (MTS/SAP)	•/•/•	•/•/•
AUDIO OUTPUT (WATTS - THD 10%)	10W + 10W	10W + 10W
SPEAKER SYSTEM	2 WAY 4 SPEAKER	2 WAY 4 SPEAKER
DOLBY DIGITAL DECODER	•	•
SURROUND SYSTEM	SRS TRUSURROUND XT	SRS TRUSURROUND XT
BASS/TREBLE/BALANCE	•/•/•	•/•/•
SOUND MODE	5 MODES ( STANDARD/MUSIC/CINEMA/SPORT/GAME)	5 MODES ( STANDARD/MUSIC/CINEMA/SPORT/GAME)
MUTE	•	•
<b>FEATURES</b>		
THX	-	-
INTELLIGENT SENSOR	•	•
DIGITAL INDEX	-	-
EPG (SI)	•	•
100HZ OSD DEMO	-	-
AUTO DEMO	•	•
ENERGY SAVING MODE (+ MODULE DPM)	•	•
CLEAR VOICE II (VOICE ZOOM)	•	•
AV MODE	•	•
1080P SOURCE INPUT	HDMI 60P/50P/30P//24P COMPONENT 60P/50P	HDMI 60P/50P/30P//24P COMPONENT 60P/50P
AV INPUT NAVIGATION (AUTO LINK)	•	•
AUTO NAVIGATION	-	-
INPUT LABELING	•	•
SCREEN ADJUST / AUTO (MANUAL) CONFIGURE - ONLY RGB	•	•
QUICK VIEW (FLASH BACK)	•	•
PICTURE FREEZE	•	•
QUICK SET-UP GUIDE	-	-
RATING (DTV)	•	•
KEY LOCK	•	•
CLOSED CAPTION	-	-
SIMPLINK (HDMI CEC)	•	•
PAGES	1000P	1000P
TOP (TABLE OF PAGE) / FLOF / LIST	•	•
QUICK MENU	•	•
<b>CHANNEL</b>		
AUTO TUNING	•	•
PROGRAMME (CHANNEL) EDIT	•	•
PROGRAMME (CHANNEL) NAME EDIT	•	•
FAVOURITE PROGRAMME	•	•
<b>TIME/CLOCK</b>		
AUTO CLOCK	•	•
MANUAL CLOCK	•	•
ON TIMER / OFF TIMER	•	•
SLEEP TIMER	•	•
AUTO SLEEP	•	•
<b>CONNECTIVITY</b>		
AV IN	1	1
S-VIDEO IN	1	1
CI SLOT	ALL EUROPE	ALL EUROPE
USB 2.0	• (JPEG / MP3 / DIVX SD)	• (JPEG / MP3 / DIVX SD)
DIVX (HD/SD)	SD	SD
BLUETOOTH	-	-
RF IN	1	1
FULL SCART	1 (TV OUT)	1 (TV OUT)
HALF SCART	1 (MNT/DTV OUT)	1 (MNT/DTV OUT)
COMPONENT IN (Y,PB,PR) + AUDIO	1 (480I/480P/576I/576P/720P/1080I/1080P)	1 (480I/480P/576I/576P/720P/1080I/1080P)
DIGITAL AUDIO OUT (COAXIAL/ OPTICAL)	1 (OPTICAL)	1 (OPTICAL)
HDMI/HDCP INPUT (VERSION 1.3 DEEP COLOUR)	3 (480I/480P/576I/576P/720P/1080I/1080P) - 1 PORT PC MODE - SIMPLINK	3 (480I/480P/576I/576P/720P/1080I/1080P) - 1 PORT PC MODE - SIMPLINK
RGB IN (D-SUB 15PIN) - PC	1	1
PC AUDIO INPUT	1	1
RS-232C (CONTROL / SVC)	1 - CONTROL & SVC	1 - CONTROL & SVC
HEADPHONE IN	-	-
<b>POWER</b>		
VOLTAGE, HZ	100-240V, 50/60HZ	100-240V, 50/60HZ
CONSUMPTION (TYPICAL)	291W	263W / 181W
STAND-BY (CABLE CARD OFF)	0.2W	0.2W
DC OFF	0.1W	0.1W
<b>DIMENSIONS</b>		
WEIGHT (KG) 1) SET (W/O STAND, KG)	32.5KG	32.5KG / 23.3KG
2) INCLUDED STAND(KG)	35KG	35 / 25.3KG
3) PACKING (KG)	40.8KG	40.8 / 31.1KG
WXHXD (MM) 1) SET (W/O STAND, MM)	1228.5 X 772 X 78.9	(50) 1228.5 X 772 X 78.9 / (52) 1040.8 X 669.2 X 76.8
2) INCLUDED STAND (MM)	1228.5 X 824.6 X 353	(50) 1228.5 X 824.6 X 353 / (52) 1040.8 X 725.8 X 308
3) PACKING (MM)	1495 X 885 X 288	(50) 1495 X 885 X 288 / (52) 1330 X 772 X 257
BRACKET CODE	AW-50PG60MS	AW-50PG60MS
VESA DIMENSIONS	400 X 400	400 X 400